



Poshtech JC400 / JC600

Model	JC400	JC600
Table		
Table size (X/Y) mm	450x450	450x600
T-slot (size * number)	8x100x5	
Max. Table loading kg	20	
Travel		
Longitudinal travel (X) mm	400	
Cross travel (Y) mm	400	600
Headstock travel (Z) mm	150	
Spindle nose to table surface	30-180	
Spindle Center to Column	50	
Spindle		
Spindle taper	ER16	
Spindle speed (standard) rpm	24000	
Feed		
Rapid travel M/min	15/15/15	15/15/15
Min. input increment mm	0.001	
ATC		
Tool holder	ER16	
Tool storage capacity pcs	no	
Max. Tool diameter mm	13	
Max. Tool length mm	30	
Max. Tool weight kg	0.5	
Tool change time	no	
Motor		
Spindle motor Kw	1.0	
X servo motor Kw	0.4	
Y servo motor Kw	0.4	
Z servo motor Kw	0.4 B	
Machine weight and space		
Floor space mm	700x1200	700x1500
Net weight kg	370	490

* Specification is subject to be changed without notice

Standard Accessories :

- * Massive iron construction
- * 24000rpm Spindle Speed
- * Direct-coupled servo motors
- * Full splash safety guard
- * Air cooling system
- * Spindle air blast (Taper)
- * Spindle air blower
- * Auto lubrication system
- * Cycle end alarm light
- * Halogen work lamp
- * Leveling blots and pads
- * Toolkit box
- * Operation & Maintenance Manual

Optional Accessories :

- * 60000 rpm Spindle speed
- * Oil cooler for spindle
- * CNC rotary table
- * Auto Tool Length Measurement

JEOU YANG MACHINERY CO.,LTD.

NO.197,MIN-SHENG ST.,TAN-TZU

TAICHUNG,TAIWAN ,ROC.

TEL : + 886-4-2537-0971

FAX : + 886-4-2537-0984

E-mail : poshtech@ms36.hinet.net